



NORTHCONE

<b>Titel</b>	<b>DECLARATION OF PERFORMANCE NC-ECO E60 E0 108F RAL X</b>				
<b>Art nr</b>	A-01-01392	<b>Document Nr.</b>	F-01-01399	<b>Godkänt av</b>	John Löwbäck
<b>Description</b>	Crash safe pole 6 m optional RAL code	<b>Revision</b>	001	<b>Date</b>	2019-01-01
<b>E-no</b>	77 715 28	<b>Author</b>	Anders Blomqvist		

1. Crash-proof lighting pole 6 meters:

**A-01-01392 NC-ECO E60 E0 108F RAL X**

2. The lighting poles are intended to be placed at motorways and county roads, other roads, circulation (and parking spaces)  
3. Tillverkare:

**Northcone AB org nr 556795-3905**  
**Rågåkersgatan 5**  
**S-781 74 Borlänge**

-----

4. System for assessment and continuous control of performance according to  
**0402-CPR-SC1043-14**
5. The assessment document according to  
**EAD 13-12-0003-01.06**
6. Technical assessment according to  
**ETA-13/0692**
7. Assessment bodies have identification numbers and names  
**0402 RISE Sveriges Tekniska forskningsinstitut**

8. Product performance:

<b>Terrain class:</b>	II	EN 40-3-1
<b>Referensvind:</b>	26 m/s	EN 40-3-1
<b>Lastfaktor klass:</b>	A	EN 40-3-3
<b>Deflection class:</b>	2	EN 40-3-3
<b>Height pole including arm:</b>	6 m	EN 40-2
<b>Length arm:</b>	0 m	EN 40-2
<b>Arm diameter:</b>	0 mm	EN 40-2
<b>Diameter pole mark:</b>	108 mm	EN 40-2
<b>Diameter pole base:</b>	114 mm	EN 40-2
<b>Weight luminaire:</b>	12 kg	EN 40-3-3
<b>Vindarea luminaire:</b>	0,16 kvm	EN 40-3-3



NORTHCONE

DECLARATION OF PERFORMANCE NC-ECO E60 E0 108F RAL X					
<b>Titel</b>					
<b>Art nr</b>	A-01-01392	<b>Document Nr.</b>	F-01-01399	<b>Godkänt av</b>	John Löwbäck
<b>Description</b>	Crash safe pole 6 m optional RAL code	<b>Revision</b>	001	<b>Date</b>	2019-01-01
<b>E-no</b>	77 715 28	<b>Author</b>	Anders Blomqvist		

**Incoming material post:** High-strength steel 2 mm  
Reinforcement hatch  
Reinforcement base tube

**Ingredient material arm:** Tube 76 x 2,9 mm

**Strength and deflection:** By calculation EN 40-3-3  
By testing EN 40-3-2

**Corrosion protection:** High-strength steel coated with  
Magnelis® EN 10346  
Reinforcement hot-dip galvanized SS-EN 1461  
Pipes hot-dip galvanized SS-EN 1461

Assessment according to requirements EN 40-5 bilaga A  
Testing LCA and sustainability Certificate \*  
Testing and evaluation Productgaranti 20 year\*

**Passive safety class:** 70NE2 EN 12767

\*) Documents produced by Northcone which, among other things, show results from tests that form the basis for assessment in accordance with the requirements of EN 40-5 Appendix A. LCA and sustainability certificate (F-01-01295) and Product Warranty 20 years (F-01-01296).

The performance of the above product is consistent with the specified performance. This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

Signed on behalf of the manufacturer is:

  
John Löwbäck  
VD Northcone AB